

## RR1G-HC



**Brand:** Serv-Ware

**Product Code:** RR1G-HC

**Availability:** Ask for quote

**Weight:** 351.00lb

**Dimensions:** 31.90in x 26.80in x 82.70in

**Call for Price:** 717-665-3525

### Short Description

1 Door 23 cu. ft Glass Door Stainless Steel Refrigerator

### Description

### Glass Door Reach-In Refrigerator - Stainless Steel

### Features

CFC Free Refrigerant and Foam

Electronic Thermostat and Digital LED Temperature Display for Accurate Control and Easy Reading

Self-Closing Door

Magnetic Gasket can be Replaced without any Tool

Heating Element Conceal in Door Frame to Eliminate any Condensation

Material: External: S/S 430  
Bottom of Internal: S/S 304,  
Other Parts of Internal: Aluminum Painted

Serv-Ware GR Series Refrigerators are UL Safety and UL Sanitation Approved.  
Featured with aluminum painted interior  
heavy duty 304 stainless steel floor  
430 stainless steel exterior and self-closing glass doors  
digital controls with a LED readout and foamed in place polyurethane cell insulation  
Unit is shipped with wheels installed  
The bottom mounted compressor designed to hold temperatures between 33° F and 41° F

Conforms to UL471, CSA C22.2 and NSF 7 Standards.

## **Warranty**

Three Year – Parts & Labor on entire unit. Valid in United States  
Five Year – Additional Compressor, Part Only

## **Specs**

### **Dimensions**

26.8" W x 31.9" D x 82.7" H  
23 cu. ft.  
351 lbs.

### **Construction**

Exterior Material: 430 Stainless Steel  
Interior Material: Painted Aluminum 304 S/S Floor  
Insulation Material: CFC Free Foam  
Shelf Material: 3 Epoxy Coated Wire

### **Cooling**

Temperature Range: 33°F – 41°F  
Refrigerant: R290  
Defrosting: Every 6 Hours  
H/P: 3/8

Electrical  
Voltage: 115  
Amps: 6  
Hz: 60  
Phase: 1

Design ambient working temperature range: 40°F to 80°F

## Product Gallery

